



HYUNDAI

Hyundai Motor America
 10550 Talbert Avenue, Fountain Valley, CA 92708
 TEL: 714-965-3000
 MEDIA WEBSITE: HyundaiNews.com
 CORPORATE WEBSITE: HyundaiUSA.com

NEWS BUREAU

2018 KONA

ENGINE		SE	SEL	Limited	Ultimate
Type		DOHC D-CVVT (Dual Continuously Variable Valve Timing), Multi-Point Fuel Injection (MPI)		DOHC D-CVVT (Dual Continuously Variable Valve Timing), Gasoline Direct Injection (GDI)	
Materials		Aluminum block and head		Aluminum block and head	
Displacement		2.0L / 1,999 cc		1.6L / 1,591 cc	
Horsepower		147 @ 6200 RPM		175 @ 5500 RPM	
Torque (lb-ft)		132 @ 4500 RPM		195 @ 1500-4500 RPM	
Valves per cylinder		4		4	
Bore & stroke (mm)		81 X 97		77 X 85	
Compression Ratio		12.5:1		10.0:1	
TRANSMISSION		SE	SEL	Limited	Ultimate
Drive Configuration	FWD	S			
	AWD	O			
6-speed automatic w/OD lock-up torque converter, electronic shift lock system		S		-	
7-speed EcoShift DCT (Dry)		-		S	
SHIFTRONIC® manual shift mode		S		S	
Torque-vectoring by Braking		S		S	
Gear Ratios		FWD/AWD		FWD/AWD	
First		4.400 / 4.639		3.929 / 3.643	
Second		2.726 / 2.826		2.318 / 2.174	
Third		1.834 / 1.841		2.043 / 1.826	
Fourth		1.392 / 1.386		1.070 / 1.024	
Fifth		1.000 / 1.000		0.822 / 0.809	
Sixth		0.774 / 0.772		0.884 / 0.854	

Seventh		-		0.721 / 0.717	
Reverse		3.440 / 3.385		5.304 / 4.696	
Final drive		3.510 / 3.648		FWD: 4.294 / 3.174 AWD: 4.643 (1/2/4/5)/ 3.611 (3,6,7,R)	
SUSPENSION		SE	SEL	Limited	Ultimate
Front	Type	MacPherson Strut with coil springs, Gas-pressurized shock absorbers, advanced valving			
	Stabilizer Bar	S			
Rear	Type	Coupled Torsion Beam Axle (FWD) / Multi-link (AWD), Gas-pressurized shock absorbers, advanced valving			
	Stabilizer Bar	S			
STEERING		SE	SEL	Limited	Ultimate
Type		Motor Driven Power Steering (MDPS) Rack and pinion steering, column-mounted			
Overall Ratio (360 degrees)		13.8			
Turns (lock to lock)		2.5			
Turning Diameter (curb to curb, ft.)		34.8			
BRAKES/TIRES/WHEELS		SE	SEL	Limited	Ultimate
Front		Ventilated Discs			
	Size (diameter)	280 mm	305mm	305mm	305mm
Rear		Solid Discs			
	Size (diameter)	262mm	284mm	284mm	284mm
ABS with Electronic Brake-force Distribution (EBD)		4-wheels, 4-channels, 4-sensors			
Tires	205/60R16	S	-	-	-
	215/55R17	-	S	-	-
	235/45R18	-	-	S	S
	Compact Temporary Spare Tire	S			

Wheels (inches)	16 X 6.5J Alloys	S	-	-	-
	17 X 7.0J Alloys	-	S	-	-
	18 X 7.5J Alloys	-	-	S	S
EXTERIOR DIMENSIONS (in.)		SE	SEL	Limited	Ultimate
Wheelbase		102.4			
Overall length		164.0			
Overall width		70.9			
Overall height (w/ roof rails)		61.0 (61.6)			
Tread Width (front) – 16”, 17”, 18”		62.0 / 61.5 / 61.4			
Tread Width (rear) – 16”, 17”, 18”		62.4 / 61.9 / 61.7			
Overhang (front / rear)		33.3 / 28.3			
Minimum Ground Clearance		6.7			
Coefficient of Drag		0.32			
INTERIOR DIMENSIONS (in.)		SE	SEL	Limited	Ultimate
Head Room (front (with sunroof) / rear)		39.6 (38.0) / 37.8			
Leg room (front/rear)		41.5 / 34.6			
Shoulder room (front/rear)		55.5 / 54.5			
Hip Room (front/rear)		53.3 / 52.2			
EPA VOLUME (cubic ft.)		SE	SEL	Limited	Ultimate
Passenger interior volume		TBD			
Cargo capacity, rear seats up		19.2			
Cargo capacity, rear seats folded down		45.8			
Total interior volume		TBD			
CAPACITIES		SE	SEL	Limited	Ultimate

Fuel (gallons)	13.2			
Roof rails load capacity	176 lbs			
Towing Capacity	Not Recommended			
WEIGHTS (lbs.)	SE	SEL	Limited	Ultimate
Curb Weight FWD/AWD <i>(lightest)</i>	2,890 / 3,084		3,042 / 3,256	
Curb Weight FWD/AWD <i>(heaviest)</i>	3,065 / 3,259		3,126 / 3,344	
GVWR FWD/AWD	3,979 / 4,189		4,046 / 4,255	
Payload FWD/AWD <i>(lightest)</i>	915 / 930		919 / 911	
FUEL ECONOMY	SE	SEL	Limited	Ultimate
FWD/AWD	City	TBD		TBD
	Highway	TBD		TBD
	Combined	TBD		TBD